

IN THE CLAIMS

1. (Previously Presented) An apparatus for facilitating a transparent service ~~option~~ transition between a first communication device and a second communication ~~device~~, comprising:
 - said first communication device, comprising:
 - a processor for establishing a first communication with said second communication device using a first service option, said second communication device identified by a first identification code;
 - a storage device for storing a second identification code also corresponding to said second communication device; and
 - said processor further for terminating said first communication and for automatically initiating said second communication with said second communication device using said second identification code, said second communication using a second service option.
2. (Original) The apparatus of claim 1 wherein said identification code comprises an alpha-numeric code associated with said first communication device for use in communications using said second service option.
3. (Original) The apparatus of claim 1 wherein said second communication is initiated within a predetermined time period.
4. (Currently Amended) The apparatus of claim 1 further comprising:
 - a receiver for receiving said second identification code during said first communication;
 - said processor further for storing said second identification code in said storage device.
5. (Currently Amended) The apparatus of claim 4 further comprising a DTMF demodulator for demodulating said second identification code.
6. (Original) The apparatus of claim 1 further comprising:
 - a countdown timer for determining the time between terminating said first communication and the initiating of said second communication;

wherein a communication from a third communication device is rejected if said countdown timer has not expired.

7. (Cancelled)
8. (Currently Amended) A method for facilitating a transparent service option transition between a first communication device and a second communication device, comprising:
 - establishing a first communication with said second communication device using a first service option;
 - transmitting a request to transition said first communication to a second communication using a second service option; and
 - transitioning said first communication to said second communication^{[[5]]}, wherein said transitioning comprises:
 - retrieving an identification code corresponding to said second communication device from a storage device located within said first communication device;
 - terminating said first communication;
 - initiating said second communication using said identification code to identify said second communication device.
9. (Previously Presented) The method of claim 8 wherein the step of initiating said second communication comprises establishing said second communication within a predetermined period from the time said first communication was terminated.
10. (Previously Presented) The method of claim 8 wherein the step of retrieving said identification code further comprises the steps of:
 - receiving said identification code from said second communication device; and
 - storing said identification code in a storage device within said first communication device.
11. (Previously Presented) The method of claim 10 further comprising the step of using DTMF demodulation to demodulate said identification code prior to the step of storing said identification code in said storage device.
12. (Cancelled)